



CPR Declaration of Performance (DoP)

DoP reference:

B2 DOP

1. Unique identification code of the product type (in combination with point 2):

BS EN 771-3:2011+A1:2015 Aggregate concrete masonry units (Dense and lightweight aggregates)

2. Identification of the construction product:

7.3N/mm² Hollow Block (see dimensions within the CE Mark & DoP insertion)

3. Intended use:

BS EN 771-3:2011+A1:2015

Masonry Units. Category II - In masonry walls, columns and partitions

4. Company name:

Hoddam Contracting Company Limited

Hoddam Road

Ecclefechan

Lockerbie

United Kingdom

DG11 3BY

5. Authorised representative:

Laura Gilfillan (address as above)

6. System of assessment:

Attestation Level 4

7. Standard and notified body:

Not applicable. Attestation Level 4

8. European Technical Assessment (ETA):

Not applicable

continued...

9. Declared performance:

Product description: 7.3N/mm ² Hollow Block		
Intended use: Masonry Units. Category II - In masonry walls, columns and partitions		
Attestation Level 4		
Essential Characteristics	Declared values	Test method
Dimension	See applicable listing (below): (l*h*w) - mm 440*215*215 440*215*140 440*140*215	Designation as section 5.2.1 BS EN 771-3:2011+A1:2015
Dimension tolerances	Tolerance - D1 / Bed Flatness & Plane parallelism - NPD	Designation as section 5.2.2 BS EN 771-3:2011+A1:2015
Configuration	Group 1 unit EN 1996-1-1	Designation as section 5.3.1 BS EN 771-3:2011+A1:2015
Compressive strength	7.3N/mm ² Cat II - Bedface	Designation as section 5.5.1 BS EN 771-3:2011+A1:2015
Moisture movement	NPD	Designation as section 5.9 BS EN 771-3:2011+A1:2015
Shear bond strength	NPD	Designation as section 5.12 BS EN 771-3:2011+A1:2015
Flexural bond strength	NPD	Designation as section 5.13 BS EN 771-3:2011+A1:2015
Reaction to fire	Euroclass A1 w without test	Commission Decision 96/603/EC, Section 5.11 (EN 773-3)
Water Absorption	Not to be left exposed	Designation as section 5.8 BS EN 771-3:2011+A1:2015
Water vapour permeability	NPD	Designation as section 5.10 BS EN 771-3:2011+A1:2015
Density	NPD	Designation as section 5.4.1 BS EN 771-3:2011+A1:2015
Thermal properties	NPD	Designation as section 5.6 BS EN 771-3:2011+A1:2015
Durability	Not to be left exposed	Designation as section 5.7 BS EN 771-3:2011+A1:2015
Dangerous Substances	Regulatory information: Not classified as dangerous. The product contains no substances contained on either the Substances of Very High Concern (SVHC) in Annex XIV of European Regulation (EC) No. 06 (REACH); or the SVHC Candidate List	BS EN 771-3:2011+A1:2015. An informative database covering European and national provisions on dangerous substances is available via the following link: http://ec.europa.eu/enterprise/construction/cpd-ds/
Declaration of Performance	In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site http://www.hoddamcontracting.co.uk (or will be supplied directly). The appropriate DoP is referenced B2 DOP on the CE Regulations page and/or on the formal documentation	CPR DoP Electronic Provision No. 305/2011


10. Declaration

The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for any on behalf of the manufacturer by Laura Gillfillan (General Manager), issued at the address given in point 4, 01 Jan 2018.

Signature: *Laura Gillfillan*

Supporting information:

The CE Mark below was issued with your delivery ticket, or accompanying documentation in accordance with the CPR regulations. Accompanying documentation may include the quotation, order acknowledgement or invoice (delivered either in hard-copy or electronic format within an email).

		BS EN 771-3:2011+A1:2015 CE Mark ref. B2 Dated 01 Jan 2018
Aggregate concrete masonry units (Dense and lightweight aggregates)		
Hoddam Contracting Company Limited		
Hoddam Road, Ecclefechan, Lockerbie, United Kingdom, DG11 3BY		
Product description: 7.3N/mm² Hollow Block		
Intended use: Masonry Units. Category II - In masonry walls, columns and partitions		
Attestation Level 4		
Essential Characteristics	Declared values	Test method
Dimension	See applicable listing (below): (l*h*w) - mm 440*215*215 440*215*140 440*140*215	Designation as section 5.2.1 BS EN 771-3:2011+A1:2015
Dimension tolerances	Tolerance - D1 / Bed Flatness & Plane parallelism - NPD	Designation as section 5.2.2 BS EN 771-3:2011+A1:2015
Configuration	Group 1 unit EN 1996-1-1	Designation as section 5.3.1 BS EN 771-3:2011+A1:2015
Compressive strength	7.3N/mm ² Cat II - Bedface	Designation as section 5.5.1 BS EN 771-3:2011+A1:2015
Moisture movement	NPD	Designation as section 5.9 BS EN 771-3:2011+A1:2015
Shear bond strength	NPD	Designation as section 5.12 BS EN 771-3:2011+A1:2015
Flexural bond strength	NPD	Designation as section 5.13 BS EN 771-3:2011+A1:2015
Reaction to fire	Euroclass A1 w without test	Commission Decision 96/603/EC, Section 5.11 (EN 773-3)
Water Absorption	Not to be left exposed	Designation as section 5.8 BS EN 771-3:2011+A1:2015
Water vapour permeability	NPD	Designation as section 5.10 BS EN 771-3:2011+A1:2015
Density	NPD	Designation as section 5.4.1 BS EN 771-3:2011+A1:2015
Thermal properties	NPD	Designation as section 5.6 BS EN 771-3:2011+A1:2015
Durability	Not to be left exposed	Designation as section 5.7 BS EN 771-3:2011+A1:2015
Dangerous Substances	Regulatory information: Not classified as dangerous. The product contains no substances contained on either the Substances of Very High Concern (SVHC) in Annex XIV of European Regulation (EC) No. 06 (REACH); or the SVHC Candidate List	BS EN 771-3:2011+A1:2015. An informative database covering European and national provisions on dangerous substances is available via the following link: http://ec.europa.eu/enterprise/construction/cpd-ds/
Declaration of Performance	In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site http://www.hoddamcontracting.co.uk (or will be supplied directly). The appropriate DoP is referenced B2 DOP on the CE Regulations page and/or on the formal documentation	CPR DoP Electronic Provision No. 305/2011

Please contact us should you require any further information.